

Technical data sheet

CV Traffic 25 Modea

Cushioned vinyl flooring



Article number(s):	609 610 618 630 632 633
	643 645 649 651 652 675
	692 963 694 965 699

Pictograms / Quality seal / Certificates



Mitglied der
DGNB
Deutsche Gesellschaft für Nachhaltiges Bauen
German Sustainable Building Council

REACH

DoP number: CVJOKALM02_04

11 | 2022

Information subject to technical modification and error. All previous data sheets are no longer valid on publication of this edition.

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de

JOKA®
Natürlich schöne Räume

INKU

Technical data sheet

CV Traffic 25 Modea

Material / structure

Residential class	23 high - residential	
Commercial class	34 very high - commercial	
Industrial class	41 high - industrial	
Total thickness (mm) approx.	2,00	
Wear layer (mm) approx.	0,70	
Surface coating	PUR - Hyperguard +	
Weight per unit area (g/m ²) approx.	2.534	
Available widths (cm)	200 + 400	
Backing design	Foam backing	
Installation direction	rotated	Colour: 609, 610, 618, 630, 632, 633, 643, 645
		649, 651, 652, 675, 692, 693, 694, 695, 699
Repeat L x W (cm)	100 x 100	Colour: 632, 675, 692, 694, 699
	99.5 x 120	Colour: 618, 633, 643, 645, 649
	100 x 120	Colour: 610, 651, 652, 693
	200 x 150	Colour: 609, 630, 695

Product characteristics

Reduction of impact sound (dB) approx.	7
Dimensional stability (%)	≤ 0.05
Static indentation behaviour (mm)	≤ 0.05
Underfloor heating	Suitable for hot water underfloor heating
Lightfastness	≥ 6
REACH	The current requirements are met
Chemical resistance	Resistant against the usual dilute household acids and alkalis.
Phthalate-free	No
Binding agent content	Type I
Suitability for chair castors	yes (type W)
Fire class	B _{fl} -s1
Skidding behaviour	R10/DS
Thermal resistance approx.	0.0108 m ² xK/W
Guarantee	5 years